

Standard configuration of PLUS-330		
Item	Module	Marks
PLUS-330	Unwind	Max unwind dia.700mm; Air expanding mandrel 3"; roll lift
	Web guide	BST/E+L Web guide (Edge position control)
	Semi/full rotary die cutting	(152T)
	Flat bed die cutting	Eye mark sensor,height of the blade 9.5mm(with upper blade and the bottom blade )
	Flat bed hot stamping	Eye mark sensor,the place of the cutting board and the foil gold can be exchanged
	Flexo printing	Eye mark sensor,semi/full rotary,(1 printing roller and 1 anilox roller)
	Rotary silk screen	Eye mark sensor
	Flat bed silk screen printing	Eye mark sensor
	Rewind	Single rewind, max unwind dia.700mm; Air expanding mandrel 3"
	Waste matrix	Max unwind dia.600mm; Air expanding mandrel 3"
Options of PLUS-330		
Item	Module	Marks
	Unwind	Max unwind dia.≥900mm; Air expanding mandrel 3", (Pneumatic feeding)
	Web guide	BST/E+L Web guide(Edge position control)
		BST/E+L Web guide (Edge/line position control)
	Corona	Vetephone
		Shuman
	Web cleaner	One side(Hefeng)
		Both sides(Hefeng)
		One side(TEKNEK)
		Both sides(TEKNEK)
	Laminator	Laminate with glue (Max unwind dia.400mm)
		Laminate with carrier (Max unwind dia.400mm)
		Movable de-lam and re-lam
		Hot laminator (Max unwind dia.400mm)
	Semi/full rotary die cutting	IML,height of the blade 0.48mm, with collection table
		Hydra Jacks
	Electro static elimination device	Mainly for static elimination
	Flat bed hot stamping	Honeycomb plate(depth 7mm)
		Aluminum plate(depth 2mm)
		Register Hologram Stamp

PLUS-330

Flexo Printing	Eye mark sensor, full rotary,(1 printing roller and 1 anilox roller)
	Adhesive printing with turn bar
	Moveable web turn bar
	Chill drum
	Ink recycle system(peristaltic pump fountain)
	Chill drum(only for full rotary)
	Chill drum control cabinet
	UV dryer(Taiwan)
	Infrared/oven drying device(Taiwan)
Rotary silk screen	Without eye mark sensor
	UV dryer
Flat bed silk screen printing	UV dryer
Laser die cutting	Eye mark sensor
Digital ink jet printing	Platform
Slitting	Min slitting width 16mm(6sets blades)
Sheeting	With collection table
	Without collection table
Back scorer	Edge trimming(2sets razor)
Rewind	Max unwind dia.≥900mm; Air expanding mandrel 3", (Pneumatic feeding)
	Twin rewind, max rewind dia. 450mm( both work)